



1 Identification of the substance/mixture and of the company/undertaking

· **Product details**

· **Trade name:** 13038 Color Coat Flattener

· **Article number:** 13038

· **Application of the substance / the preparation** COATING

· **Manufacturer/Supplier:**

SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225

· **Further information obtainable from:**

cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT

· **Information in case of emergency:** 24 HR EMERGENCY CHEMTREC 1-800-424-9300

2 Hazards identification

· **Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Xn; Harmful

R48/20-63: Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child.



Xi; Irritant

R36/38: Irritating to eyes and skin.



F; Highly flammable

R11: Highly flammable.

R67: Vapours may cause drowsiness and dizziness.

(Contd. on page 2)



Trade name: 13038 Color Coat Flattener

(Contd. of page 1)

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word Danger**

· **Hazard-determining components of labelling:**

toluene

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**



Xn Harmful

F Highly flammable

· **Hazard-determining components of labelling:**

toluene

· **Risk phrases:**

11 Highly flammable.

36/38 Irritating to eyes and skin.

48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

(Contd. on page 3)

**Trade name: 13038 Color Coat Flattener**

(Contd. of page 2)

- 63 Possible risk of harm to the unborn child.
67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 9 Keep container in a well-ventilated place.
16 Keep away from sources of ignition - No smoking.
36/37 Wear suitable protective clothing and gloves.
60 This material and its container must be disposed of as hazardous waste.

3 Composition/information on ingredients**· Chemical characterization****· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 108-88-3 EINECS: 203-625-9	toluene Xn R48/20-63-65; Xi R38; F R11 R67 Repr. Cat. 3 Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	40 - 60%
CAS: 2807-30-9 EINECS: 220-548-6	2-(propyloxy)ethanol Xn R21; Xi R36 R10 Acute Tox. 4, H312; Eye Irrit. 2, H319	10 - 13%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate R10 Flam. Liq. 3, H226	10 - 13%
CAS: 9011-05-6	Urea polymer Xn R22; Xi R36/37/38 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	7 - 10%
CAS: 78-93-3 EINECS: 201-159-0	butanone Xi R36; F R11 R66-67 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5 - 7%
	Silica Xi R36/37/38 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
	ORGANIC DERIVATIVE OF CASTOR OIL Xi R36/37 Eye Irrit. 2, H319; STOT SE 3, H335	1-1.5%

· Additional information: For the wording of the listed risk phrases refer to section 16.**4 First aid measures**

- After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
· After skin contact: Immediately wash with water and soap and rinse thoroughly.
· After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 4)



Trade name: 13038 Color Coat Flattener

(Contd. of page 3)

· **After swallowing:** If symptoms persist consult doctor.

5 Firefighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

108-88-3 toluene

WEL ()	Short-term value: 384 mg/m ³ , 100 ppm
	Long-term value: 191 mg/m ³ , 50 ppm
Sk	

108-65-6 2-methoxy-1-methylethyl acetate

WEL ()	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
Sk	

(Contd. on page 5)



Trade name: 13038 Color Coat Flattener

(Contd. of page 4)

78-93-3 butanone

WEL ()	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
Sk	

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes and skin.
- **Respiratory protection:**
 - In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 - The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **General Information**
- **Appearance:**
 - Form:** Liquid
 - Colour:** According to product specification
 - Odour:** Characteristic
- **Change in condition**
 - Melting point/Melting range:** Undetermined.
 - Boiling point/Boiling range:** 79°C
- **Flash point:** -4°C

(Contd. on page 6)



Trade name: 13038 Color Coat Flattener

(Contd. of page 5)

· Ignition temperature:	230°C
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	23.3 Vol %
· Vapour pressure at 20°C:	29 hPa
· Density at 20°C:	0.97 g/cm ³
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Solvent content:	
Organic solvents:	73.7 %
VOC (EC)	718.4 g/l
· Solids content:	25.2 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Materials to be avoided:**
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

· LD/LC50 values relevant for classification:		
108-88-3 toluene		
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

GB

(Contd. on page 7)



Printing date 28.10.2010

Revision: 28.10.2010

Trade name: 13038 Color Coat Flattener

(Contd. of page 6)

12 Ecological information

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**

- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**



- **ADR/RID class:** 3 Flammable liquids.

- **Danger code (Kemler):** 33

- **UN-Number:** 1263

- **Packaging group:** II

- **Hazard label:** 3

- **Description of goods:** 1263 PAINT, special provision 640D

- **Tunnel restriction code D/E**

- **Maritime transport IMDG:**



- **IMDG Class:** 3

- **UN Number:** 1263

- **Label** 3

- **Packaging group:** II

- **EMS Number:** F-E,S-E

- **Marine pollutant:** No

- **Proper shipping name:** PAINT

(Contd. on page 8)

GB



Trade name: 13038 Color Coat Flattener

(Contd. of page 7)

· **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label** 3
- **Packaging group:** II
- **Proper shipping name:** PAINT

· **UN "Model Regulation":** UN1263, PAINT, 3, II

15 Regulatory information

- **Chemical safety assessment** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- R10 Flammable.
- R11 Highly flammable.
- R21 Harmful in contact with skin.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R36/37 Irritating to eyes and respiratory system.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R38 Irritating to skin.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R63 Possible risk of harm to the unborn child.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** Environment protection department.
- **Contact:** Steve Gaver

(Contd. on page 9)



Printing date 28.10.2010

Revision: 28.10.2010

Trade name: 13038 Color Coat Flattener

(Contd. of page 8)

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

GB